



Tri-Max

3.00 – 6.30 m



Heavy duty stubble cultivator



TriMax

Tri-Max is a new heavy duty stubble cultivator. Tri-Max consists of 3 rows of tines, angled levelling discs and a T-ring roller. A full cut is achieved when the implement is fitted with 300 mm wide winged shares. The specially designed share perfectly incorporates the stubble and plant residues. The 85 cm clearance height allows large volumes of trash to flow through the machine even at working depths of 25 cm. The angled discs mix the residue with soil and leave the surface level and smooth. The T-ring roller controls the depth and consolidates the ground. Optional: (3 m model) 400 mm flat steel crumbler For mounting behind the T-ring roller.



Disc



600 mm T-ring roller: T-stål



Tri-Max NSH with 2 D tines and 50x20 mm point



120 mm wide wing share

Tri-Max Classic with shear bolts

Type	3,0 m mounted	4,10 m mounted	4,70 m hydr.
Working width	3,00 m	4,10 m	4,70 m
Nos of tines	11	15	17
Nos of discs	8	11	15
Weight	1550 kg	2460 kg	3400 kg
Hp required	160 hp	225 hp	250 hp
Nos of sections	1	1	3
Working speed	8-12 km/h	8-12 km/h	8-12 km/h
Hydraulic services	0	0	1 DW
LED light kit	Optional	Optional	Optional
50 mm points for deep work	Optional	Optional	Optional
120 mm point with wing shear	Standard	Standard	Standard

Tri-Max NSH 2-D stone security

Type	3,0 m mounted	4,10 m mounted	4,10 m hydr.
Working width	3,00 m	4,10 m	4,10 m
Nos of tines	11	15	15
Nos of discs	8	11	11
Weight	2050 kg	2750 kg	3000 kg
Hp required	160 hp	225 hp	225 hp
Nos of sections	1	1	2
Working speed	8-12 km/h	8-12 km/h	8-12 km/h
Hydraulic services	1 EW	1 EW	2 DW
LED light kit	Optional	Optional	Optional
50 mm points for deep work	Optional	Optional	Optional
120 mm point with wing shear	Standard	Standard	Standard

Tri-Max semi-mounted NSH 2-D stone security

Type	6,30 m hydr.
Working width	6,30 m
Nos of tines	23
Nos of discs	17
Weight	8500 kg
Hp required	400 hk
Nos of sections	3
Working speed	8-12 km/h
Hydraulic services	4 DW
LED light kit	Standard
Wheels	600/50-22,5 twin
Transport width	3 m
Transport height	4 m
50 mm points for deep work	Optional
120 mm point with wing shear	Standard

DAL-BO A/S

DAL-BO A/S | Bindeballevej 69 | DK-7183 Randbøl
 Tlf.: +45 75 88 35 00 | Fax: +45 75 88 31 57
 E-mail: info@dal-bo.dk | www.dal-bo.dk

